

# TILLAGE AND SEEDING



**WOODS**

# THERE'S NOTHING LIKE THE SMELL OF FRESH TURNED DIRT AND THE HOPE OF NEWLY PLANTED SEEDS

## TABLE OF CONTENTS

### QUICK HITCH ..... 3

Woods Quick Hitch makes easy work of changing from one 3-point attachment to another.

### ROTARY TILLERS ..... 4

Woods' line of forward and reverse rotation tillers couple the best design features with outstanding performance for your landscaping and gardening projects.

### DISC HARROWS ..... 6

Whether breaking ground or tilling existing plots, Woods disc harrows are a rugged must-have tool for gardens, nurseries, food plots and small-acreage farms.

### SEEDERS ..... 7

The versatile family of seeders come in a range of sizes and can handle primary seeding, over-seeding, inter-seeding, and applications such as native grasses and food plots.

### Your Woods Dealer

Our products are distributed and backed by a network of authorized Woods dealers because we believe in the expertise and service you can only get from an experienced, specialized retailer. From the moment you walk into the showroom and for years to come, your Woods dealer will help you select the right equipment and offer follow-up service and maintenance.

To find your nearest store visit us at [woodsequipment.com](http://woodsequipment.com) or call 800-319-6637.

# Woods

## GENUINE PARTS



Since our founding in 1946, Woods has built a strong reputation for manufacturing equipment with superior design and durability. So when it comes to keeping your equipment in top condition, there's only one choice. Woods Genuine Parts are designed for the best performance on your Woods equipment, not simply to "fit." We stand behind the quality of our replacement parts. And, our network of knowledgeable dealers is essential to not only get you the parts you need today, but to maintain your machine and keep you going for years to come.

### 3 TIPS FOR CHOOSING THE RIGHT ATTACHMENT

- 1. Consider the work and frequency.** Your job and how often you do it will determine the right attachment. For example, how many acres do you mow and how often? Do you need a finish mower for a fine cut or a rotary cutter for tall grass and brush?
- 2. Match the attachment to your tractor horsepower.** Your tractor needs enough horsepower to properly run the attachment and maximize its performance, but not too much horsepower or you could damage the implement. Match the "hp range" of your tractor and the equipment.
- 3. Ensure the attachment is wider than your tractor's rear tires.** When mowing and working the dirt it's best to have the implement cover the rear tire tracks, especially when trimming and working along edges. It leaves a smoother and more uniform appearance.

## QUICK HITCH

**Woods quick hitches make easy work of changing from one 3-point attachment to another. When hooking up to many implements, you never have to leave the tractor because lower hooks automatically lock implement into place.**

- Heavy-duty steel construction with adjustable top link bracket
- 7/8-inch diameter mounting pins and adapter bushings
- Lower arms lock automatically
- Ensure fast, easy and safe hook-ups with ASABE quick-hitch compatibility



SPECIFICATIONS	TQH1	TQH2
Tractor Hitch	CAT 1	CAT 2
Width (in)	27.25	27.25
Approximate Weight (lbs)	75	75
Mounting Pin Diameter (in)	.875	.875
Adapter Bushing Diameter (in)	1.125	1.125



# WHY CHOOSE A WOODS ROTARY TILLER?



Woods' innovative double flange design strengthens blade support and simplifies maintenance.

Robust gear-driven side drive provides years of reliable service and requires far less maintenance than chain-driven units.

Woods 3-year input gearbox warranty includes seals.



Heat-treated, C-shaped tines penetrate deep, even in thick residue and loose, compacted or rocky soil.



Tapered tailgate removes furrow for a finished seedbed.

Adjustable skid shoes provide easy depth control.

Fixed offset tiller width covers tire tracks with each pass.



Sturdy tubular integrated parking stand ensures easy storage and hook-up.





## ROTARY TILLERS

Woods' line of rotary tillers couples the best design features with outstanding performance for the discerning user. Choose forward or reverse rotation for the best performance depending on the type of soil.



**TRACTOR HP RANGE:**  
**12 - 35 HP**

### 30-Series Rotary Tillers

**Models**

**RT42.30** | 41-inch  
**RT48.30/RTR48.30** | 47-inch

**TRACTOR HP RANGE:**  
**18 - 50 HP**

### 40-Series Rotary Tillers

**Models**

**RT60.40/RTR60.40** | 59-inch  
**RT72.40/RTR72.40** | 71-inch



**▶ VIDEO**

- Innovative double-flange design for blade support
- Gear-driven side drive – less maintenance than chain-driven units
- 3-year warranty on input gearbox (includes seals)
- Rugged, heat-treated c-shaped tines for deep penetration in the toughest soils
- Tapered tailgate removes furrow for a finished seedbed
- Sturdy tubular integrated parking stand for easy storage and setup
- 30- and 40-series models available as either forward or reverse rotation
- On initial pass reverse rotation tillers will often till deeper and faster than forward rotation models
- Slip clutch driveline protection is standard on all models
- Skid shoes standard





## Woods offers tillers in forward or reverse rotation in 42"—74" widths.

Forward rotation tillers are ideal for moist, wet, rocky, sandy or loose soil conditions. Reverse rotation tillers work best in non-rocky soil conditions. They deliver a smoother top layer of soil by allowing ground cover to travel over the rotor top first, then incorporating it back into the ground beneath a fresh new layer of dirt. More often than not, users can achieve an exceptional seed bed with fewer passes when using a reverse rotation tiller.



SPECIFICATIONS	RT42.30	RT48.30/ RTR48.30	RT60.40/ RTR60.40	RT72.40/ RTR72.40
Tractor PTO (hp)	12-30	15-35	18-40	20-50
Tractor Hitch	Limited CAT 1 & CAT 1		CAT 1	
Working Width (in)	41	47	59	71
Overall Width (in)	51	57	69	81
Weight (lbs)	478	502 / 508	570 / 578	621 / 630
Maximum Tilling Depth (in)	7			
Drive Type	Gearbox			
Total Number of Tines / Flanges	20 / 5	24 / 6	28 / 7	36 / 9
Number of Tines per Flange	4 C-type			
Rotor Speed (rpm)	210			
Tractor PTO Speed (rpm)	540			
PTO Driveline Protection	Slip clutch			
Gearbox Housing	Heavy-duty cast iron			
Gearbox Drain Plug	Yes			
Offset (left)	3" fixed		2.25" fixed	
Quick-Hitch Compatible	Yes			





## DISC HARROWS

Built with high-strength U.S. steel, these rugged disc harrows carry Woods' reputation for durability and reliability. Plus, these new discs are easy to use due to innovative design features like individually adjustable disc gangs that reposition with a single pin.

### TRACTOR HP RANGE: UP TO 55 HP

#### Models

- DHS48** 48-inch
- DHS64** 64-inch
- DHS80** 80-inch


- Mud scrapers that prevent clogging, increase productivity
- Furrow fillers (DHS64, DHS80)

### TRACTOR HP RANGE: UP TO 85 HP

#### Models

- DHM80** 80-inch
- DHM96** 96-inch

- Furrow fillers to reduce end ridges
- Rear drawbar for towing equipment
- Mud scrapers that prevent clogging, increase productivity



▶ VIDEO



SPECIFICATIONS	DHS48	DHS64	DHS80	DHM80	DHM96
Tractor Engine (hp)	Up to 35	25-45	35-55	45-75	55-85
Tractor Hitch	CAT 1, Lim. CAT 1	CAT 1		CAT 1 & 2	
Width (in)	48	64	80		96
Weight (depends on blade type) (lbs)	390	508	590	845	960
Disc Blade Type	Notched	Notched; or combination smooth and notched			
Average Weight per Blade (lbs)	33	36	33	47	44
Disc Diameter (in) / Quantity	16 / 12	18 / 14	18 / 18	20 / 18	20 / 22
Disc Spacing (in)	7.5 front and rear	9 front, 7.5 rear			
Gang Axle Diameter (in)	1 square			1 1/8 square	
Frame Construction (in)	3 x 3 tube and angle		3 x 3 tube and channel	3 x 3 tube	
ASABE Quick-Hitch Compatible	Yes				



# COMPACT SUPER SEEDERS

The Woods Compact Super Seeder is everything you need in one compact cultivation and planting package. In one pass you can prepare the seed bed, precisely drop seeds at two different depths, then firm the bed for improved germination.

## TRACTOR HP RANGE: 15 - 35 HP

**Model**  
**CSS48** | 48-inch

- Three-point hitch: CAT 1/Limited CAT 1
- Working width 48 inches
- ATV/UTV minimum 350cc

## TRACTOR HP RANGE: 20 - 45 HP

**Model**  
**CSS60** | 60-inch

- Three-point hitch: CAT 1/ Limited CAT 1
- Working width 60 inches
- ATV/UTV minimum 400cc

SPECIFICATIONS	CSS48	CSS60
Tractor Engine (hp)	15-35	20-45
Tractor Hitch	CAT 1/Limited CAT 1	
ATV/UTV Engine Size	Minimum 350cc	Minimum 400cc
Working Width (in)	48	60
Overall Width (in)	57	69
Weight with Seed, Depending upon Configuration (lbs)	395-679	487-810
Drive Type	Ground-driven spiked roller	
Number of Seed Boxes Available	1 or 2	
Seed Metering	6 seed cups	8 seed cups
Seed Box Ratio	5.1:1 or 14.4:1	5.1:1 or 14.4:1
Cool Season Seed Box with Agitator	Standard	
Cool Season Seed Box Capacity (bushel)	1	1.25
Legume Seed Box	Optional	
Legume Seed Box Capacity (bushel)	1	1.25
Front Tool Choices	6 - 16" notched disc blade or spiked roller	8 - 16" notched disc blade or spiked roller
Calibration Tray	Standard	
Crank Handle	Standard	
Spring-loaded Trailing Cultipacker	Optional	
Speed Ranges	Turf seed range 0-700 lbs/acre (cool season); Food plot range 0-30 lbs/acre (legume)	
Options	Fast/slow chain drive, Quick Hitch bushings, mud scrapers, seed stop plates, highway lights, tow kit	
ASABE Quick Hitch	Add hitch pin bushings to make CAT 1 quick-hitch compatible	

- Simultaneously plant two seed types at two different depths in one pass
- Precisely measure out seeds, reducing waste, plus enjoy the durability of metal (not plastic) meters
- Handle a wide range of seeds from Black-eyed Susans to corn
- Easily weave into narrow spaces and make tight turns to plant areas that may not be accessible with a larger tractor and planter
- Expect years of work from a rugged, Grade 80 steel body



**VIDEO**



**Ideal for small-scale planting, such as food plots, lawns, gardens, wildflower meadows, waterways and roadways. Widths 48 or 60 inches and lighter weight so you can maneuver into formerly unreachable areas.**

**Productivity** – Simultaneously plant two seed types at two different depths in one pass. **WOODS EXCLUSIVE**

**Precision Metering** – Precisely measure out seeds, reducing waste, plus enjoy the durability of metal (not plastic) meters.

**Versatility** – Handle a wide range of seeds from Black-eyed Susans to corn. See our planting guide.

**Maneuverability** – Easily weave into narrow spaces and make tight turns to plant areas that may not be accessible with a larger tractor and planter.

**Durability** – Expect years of work from a rugged, Grade 80 steel body.

**CSS60**

**Additional Features Standard on Both Models**

- The calibration system includes seed charts, a calibration tray and crank for accurate seed rates. **WOODS EXCLUSIVE**
- Windowed seed cups and clear PVC tubes allow you to easily monitor the flow of seeds.
- A quick and easy disconnect – pull a pin and one or both seed boxes stop to make it a tilling tool for preparing the ground. Till your seed bed, then replace the pin and engage the seeding function for a final pass. **WOODS EXCLUSIVE**





# PRECISION SUPER SEEDERS

Versatile and flexible to easily handle primary seeding, over-seeding, and applications such as native grasses and food plots.

**TRACTOR HP RANGE:**  
**25 - 65 HP**

**TRACTOR HP RANGE:**  
**35 - 125 HP**

**Models**

**PSS48** 49-inch  
**PSS60** 60-inch

**Models**

**PSS72** 72-inch  
**PSS84** 84-inch

- Three seed box options — cool season, warm season, and legume — let you plant anything from rye and oats to prairie grasses, wild flowers, radishes and soybeans
- Efficient, one-pass planting of up to two seed types at one depth and legume seeds at a different depth with models equipped with three seed boxes
- All seed boxes can be engaged and disengaged independently with a single lynch pin — no tools required



**PSS84**

SPECIFICATIONS	PSS48	PSS60	PSS72	PSS84
Tractor Engine (hp)	25-45	30-65	35-85	40-125
Tractor Hitch	CAT 1 & 2			
Working Width (in)	49	60	72	84
Weight with Seed, Depending upon Configuration (lbs)	1,189-2,580	1,389-3,023	1,721-3,698	1,938-4,214
Number of Seed Boxes Available	3			
Seed Metering	Fluted and picker wheel			
Seed Cups (7 in spacing)	7	8	10	12
Cool Season Seed Box Capacity (bushel)	4.00	5.00	6.00	7.00
Native Warm Season Seed Box Capacity (bushel)	5.00	6.25	7.50	8.75
Legume Seed Box Capacity (bushel)	1.00	1.25	1.50	1.75
Front Roller Spikes (in)	(128) 0.5 x 2 carbide steel	(160) 0.5 x 2 carbide steel	(192) 0.5 x 2 carbide steel	(224) 0.5 x 2 carbide steel
Disc Blades (diameter (in)   quantity)	16   8		18   10	18   12
Cast Iron or Nylon Trailing Cultipacker	Optional (9.5" diameter cast iron or 11" diameter nylon)			
Calibration Tray & Crank Handle	Standard			
Mud Scrapers & Frame Platform	Optional			
ASABE Quick-Hitch Compatible	Yes			





# FOOD PLOT SEEDERS

Plant up to three types of seed in one pass. Ideal for hunters and small acreage farmers seeding legumes and larger seeds.

**TRACTOR HP RANGE:  
25 - 125 HP**

**Models**

- FPS48**      49-inch
- FPS60**      60-inch
- FPS72**      72-inch
- FPS84**      84-inch

- Three seed box choices — one cool season and two legume — can plant a variety of seeds like alfalfa, clover, corn, sorghum, soybeans, turnips and wheat
- A trailing cultipacker firms the seed bed for perfect seed-to-soil contact that's ready to trap moisture for germination
- Plant cool season seeds, in rows, at a deeper depth while evenly broadcasting up to two types of legume seeds at a shallow depth — all in one pass



**▶ VIDEO**



SPECIFICATIONS	FPS48	FPS60	FPS72	FPS84
Tractor Engine (hp)	25-45	30-65	35-85	40-125
Tractor Hitch	CAT 1 & CAT 2			
Working Width (in)	49	60	72	84
Weight with Seed, Depending upon Configuration (lbs)	1,042-2,098	1,181-2,436	1,463-2,990	1,629-3,426
Number of Seed Boxes Available	3			
Seed Box Ratio	1-speed			
Seed Cups (7 in spacing)	7	8	10	12
Row Units	Standard			
Cool Season Seed Box Capacity (bushel)	4.00	5.00	6.00	7.00
Legume Seed Box Capacity (bushel)	1.00	1.25	1.50	1.75
Disc Blades (diameter (in)   quantity)	16   8		18   10	
Cast Iron or Nylon Trailing Cultipacker	Optional (9.5" diameter cast iron or 11" diameter nylon)			
Calibration Tray & Crank Handle	Standard			
Mud Scrapers & Frame Platform	Optional			
ASABE Quick-Hitch Compatible	Yes			



## Got ideas?

Join our Power Team customer panel at [woodsequipment.com/contact/power-team](http://woodsequipment.com/contact/power-team), or scan the QR code to the right.

**You have the power...**



**WOODS®** | Woods Equipment Company  
2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 [woodsequipment.com](http://woodsequipment.com)

**WOODS**  
**GET AFTER IT**

Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2022 Woods Equipment Company. All rights reserved. WOODS and Woods logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.

**B101803** Revised June 2022