

# WOODS *New* 30- & 40-SERIES ROTARY TILLERS

## SIZES

42 inches, 48 inches, 60 inches, 72 inches



Woods' latest series of Rotary Tillers are durable and simple to maintain. Precision engineering, top quality materials, and state-of-the-art manufacturing techniques make them a high-quality, affordable, and productive tool for a wide variety of tilling tasks.

**Our 30- and 40-series Rotary Tillers are available in widths from 42" to 72", compatible with tractor HP from subcompact up to utility (50 HP). Available in either forward or reverse rotation.**

### Woods Rotary Tillers are ideal for:

- Vegetable gardens
- Small-acreage farming
- Hunting food plots
- Landscape maintenance

### Configure your Woods Rotary Tiller for any job:

- Choose a forward-rotation unit for low horsepower tractors and/or rocky soil conditions.
- Choose a reverse-rotation unit to work the soil more aggressively and leave a finer finish in fewer passes.
- All Rotary Tillers come factory-configured for a single tilling direction. No complicated, time-consuming modifications necessary.
- Woods products are painted with a heat-cured powder coat finish – available from the factory in green, orange, red or blue to match your tractor.

# Woods 30- & 40-Series Rotary Tillers

Specifications	RT42.30 forward	RTR42.30 reverse	RT48.30 forward	RTR48.30 reverse	RT60.40 forward	RTR60.40 reverse	RT72.40 forward	RTR72.40 reverse
<b>Tractor PTO HP</b>	up to 30 hp		up to 35 hp		20-40 hp		20-50 hp	
<b>Tractor Hitch</b>	Lim Cat 1 and 1		Lim Cat 1 and 1		Cat 1		Cat 1	
<b>Working Width</b>	41"		47"		59"		71"	
<b>Overall Width</b>	51"		57"		69"		81"	
<b>Weight</b>	478 lbs		502 lbs		578 lbs		630 lbs	
<b>Maximum Tilling Depth</b>	7"							
<b>Drive Type</b>	gearbox							
<b>Total No. of Tines / Flanges</b>	20 / 5		24 / 6		28 / 7		36 / 9	
<b>No. of Tines per Flange</b>	4 C-type							
<b>Rotor Speed</b>	210							
<b>Tractor PTO Speed</b>	540							
<b>PTO Driveline Protection</b>	slip clutch							
<b>Gearbox Housing</b>	heavy-duty cast iron							
<b>Gearbox Drain Plug</b>	yes							
<b>Offset (left)</b>	3"				2.25"			
<b>Quick-Hitch Compatible</b>	yes							
<b>Standard-duty</b>								



Woods' innovative double flange design strengthens blade support and simplifies maintenance.



Sturdy tubular integrated parking stand ensures easy storage and hook-up.

## Why choose a Woods Rotary Tiller?

Robust gear-driven side drive provides years of reliable service and requires far less maintenance than chain-driven units.

Woods 3-year input gearbox warranty includes seals.



Heat-treated, C-shaped tines penetrate deep, even in thick residue and loose, compacted or rocky soil.



Fixed offset tiller width covers tire tracks with each pass.

Adjustable skid shoes provide easy depth control.

Tapered tailgate removes furrow for a finished seedbed.

**WOODS®**

2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 woodsequipment.com

Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2016 Woods Equipment Company. All rights reserved. WOODS and Woods logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.

**WOODS**